

Fresh



Breton

Italian Porcelain

12x24 Matte & Polished, 24x24 Matte & Polished, 2x2

Mosaics, 4x4.5 Hexagon Mosaic Honed


TILE

AMERICA

SHADE VARIATION

V2 - Slight Variation

Clearly distinguishable differences in texture and/or pattern within similar colors.



Bloom



WEAR CODE

All Breton matte finish is rated (5) for all residential and commercial applications. Bloom/Fresh/Street Polished are rated (4) for all residential and light commercial applications.

Glow Polished is rated (3) for all residential applications.

Frame/Board Polished is rated (2) for light residential applications.

Street



PERFORMANCE DATA

THICKNESS: 9.00 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5 % (Matte)
Abrasion Resistance	ISO 10545-7	5 (Matte)
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction	AcuTest	≥ 0.42 (Matte)
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. Class B
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Min. Class 3

Frame



Board



Glow



Notes:

Dynamic Coefficient of Friction (DCOF) for the matte finish is > 0.42 Wet. Minimum Recommended Grout Joint for Rectified tiles is no less than 1/8". Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

Book An Appointment



www.tileamerica.com