


White Hexagon



CC Mosaics II


Porcelain Mosaics
12x12 Sheets

TILE AMERICA


SHADE VARIATION

V2 - Slight Variation

Clearly distinguishable differences in texture and/or pattern within similar colors.



White & Black Hexagon



WEAR CODE

All sizes with Grey dot: Rated 5 for all residential and light commercial applications.
All sizes with Black dot: Rated 2 for light residential applications only.

White Basketweave With Black Dot




PERFORMANCE DATA


THICKNESS: From 6.00 mm

Characteristic:	Norms:	Results
Water Absorption	C373	≤ 0.5 %
Deep Abrasion (Unglazed)	C1243	-
Breaking Strength	C648	Min. 290
Dynamic Coefficient of Friction Wet	A137.1	≤ 0.21
Dimensions	C499	Conforms
Facial Range of Thickness	C499	Conforms
Warpage (Diagonal)	C485	Conforms
Wedging	C502	Conforms
Frost Resistance	C1026	Frost Resistant
Scratch Hardness	MOHS	3


White Basketweave With Grey Dot



White Octagon With Black Dot



White Octagon With Grey Dot



Notes:

The Dynamic Coefficient of Friction for these mosaics is approximately 0.30 Wet.
Always inspect materials prior to installations.
Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com