

Diamond Herringbone



# Porcelain Mosaics


Glazed  
12x12 Sheets

# TILE AMERICA

White Octagon  
w/White Dots




1" Hexagon  
Matte & Polished




Bright White  
Lantern




White and Grey  
Diamond Penny  
Round





White and Black  
Diamond Penny  
Round




"2 White, Grey & Black  
Hexagon  
Matte & Glossy




White, Grey, Black  
Penny Round  
Matte & Glossy



Red, Cobalt  
Bright Penny Round




White Pinwheel  
w/Black Dot



## SHADE VARIATION

V1 - Uniform Appearance  
Differences among pieces from the same production run are minimal.



## WEAR CODE

Light Residential Use. Must not be used in residential areas that are subject to constant or heavy traffic.

## PERFORMANCE DATA

THICKNESS: From 6.00 mm

Characteristic:	Norms:	Results
Water Absorption	C373	≤ 0.5 %
Deep Abrasion (Unglazed)	C1243	-
Breaking Strength	C648	Min. 290
Dynamic Coefficient of Friction Wet	A137.1	≤ 0.21
Dimensions	C499	Conforms
Facial Range of Thickness	C499	Conforms
Warpage (Diagonal)	C485	Conforms
Wedging	C502	Conforms
Frost Resistance	C1026	Frost Resistant
Scratch Hardness	MOHS	3

## Notes:

The Dynamic Coefficient of Friction for these mosaics is approximately 0.30 Wet.  
Always inspect materials prior to installations.  
Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment

