


DIAMOND
HERRINGBONE



OCTAGONS
W/DOTS




1" HEXAGONS



LANTERNS








DIAMOND
PENNY
ROUNDS



2" HEXAGONS



PENNY ROUNDS



PINWHEEL

PORCELAIN TILE


MOSAICS

AMERICA

Glazed
12x12 Sheets

SHADE VARIATION

V1 - Uniform Appearance
Differences among pieces from the same production run are minimal.



WEAR CODE

Light Residential Use. Must not be used in residential areas that are subject to constant or heavy traffic.

PERFORMANCE DATA

THICKNESS: From 6.00 mm

Characteristic:	Norms:	Results
Water Absorption	C373	≤ 0.5 %
Deep Abrasion (Unglazed)	C1243	-
Breaking Strength	C648	Min. 290
Dynamic Coefficient of Friction Wet	A137.1	≤ 0.21
Dimensions	C499	Conforms
Facial Range of Thickness	C499	Conforms
Warpage (Diagonal)	C485	Conforms
Wedging	C502	Conforms
Frost Resistance	C1026	Frost Resistant
Scratch Hardness	MOHS	3

Notes:

The Dynamic Coefficient of Friction for these mosaics is approximately 0.30 Wet.
Always inspect materials prior to installations.
Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com