

Ivory



Canton

Italian Porcelain

12x24, 24x24, 9.5x11 Hexago, 2.75x3.25 Hexagon

Mosaics, 12x12 Intreccio Mosaic, 2.5x24 Battiscopa


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example “that little bit of color” on one piece of tile may be the primary color on the next piece.



Brown



WEAR CODE

Canton Grey and Ivory are rated (5) for all residential and commercial applications.
Canton Black and Brown are rated (4) for all residential and most commercial applications.

PERFORMANCE DATA

THICKNESS: 9.50 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.1%
Abrasion Resistance	ISO 10545-7	4 / 5
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	A-LA-HA
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	A-LA-HA
Scratch Hardness	MOHS	> 6
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resists

Grey



Black



Notes:

Dynamic /Coefficient of Friction (DCOF) is > 0.42 Wet.

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15” should not be staggered more than 1/3 the length of the tile.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representation only.

Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

Book An Appointment



www.tileamerica.com