

Cotton



Concrete




Mud



Sand/Sunflower




Ocean



Pine Green



Carbon



# Coventry

Italian Porcelain

3x16, 2x3 Hexagon Mosaic, 12x24 Modernist,  
2x2 Mosaic, 12x24, 3x24 Bullnose


# TILE

AMERICA

SHADE VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

V2 - Slight Variation



WEAR CODE

Coventry 12x24, Modernist, Hexagons and  
2x2s are rated (5) for all residential and commercial applications.

Coventry 3x16 is rated (1) for walls only.

## PERFORMANCE DATA

THICKNESS: 8.50 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	0.10%
Deep Abrasion	ISO 10545-6	135 mm <sup>3</sup>
Breaking Strength	ISO 10545-4	≥ 35N/mm <sup>2</sup>
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance- Household Chemicals	ISO 10545-13	Min. Class GB
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Min. Class 3

## Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An  
Appointment



www.tileamerica.com