# T | L E 🔶 A M E R I C A<sup>®</sup>

COLOR



Inspired by the most classic of Italian marbles, Carrara has a clean white background with soft grey veining. The elegant simplicity is perfect for today's design aesthetic. Carrara is offered in a 12x24 format, with 2x2mosaic and 3x24 trim in both matte and polished finishes. There is also a 9x24 glossy wall tile and a pre-scoured 9x24 to create a 4x8 faux brick look. The brick version can be stacked or staggered to create two different stunning looks.

### SIZE

#### 2x2 mosaic

Finish: matte or polished Thickness: 10 mm

#### 12x24


Finish: matte or polished Thickness: 10 mm

#### 9x24

Finish: polished Thickness: 10 mm


#### **9x24 frame brick** Finish: polished Thickness: 10 mm

#### carrara grey matte





#### carrara grey polished









# T | L E 🔶 A M E R I C A<sup>®</sup>

## **CARRARA** TECHNICAL INFORMATION

### SHADE VARIATION

**V2 - Slight Variation** Clearly distinguishable differences in texture and/or pattern within similar colors.

## WEAR CODE

Matte Finish: 4 - Rated for all residential and light commercial applications.

Polished Finish: 5 - Rated for all residential and commercial applications.

**Glossy Finish: 1** - Rated for all residential applications.

## PERFORMANCE DATA

CHARACTERISTIC	NORMS	12x24, 2x2 MATTE	12x24, 2x2 POLISHED	9X24 WALL
Water Absorption	ISO 10545-3	<0.5%	<0.5%	NA
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4	3	1
Breaking Strength	ISO 10545-4	>35N/mm2	>35N/mm2	>15N/mm2
Static Coefficient of Friction Wet	C1028	0.50	0.50	NA
Dimensions Range	ISO 10545-2	Conforms	Conforms	Conforms
Frost Resistance	ISO 10545-12	Frost Proof	Frost Proof	No
Chemical Resistance - Household Chemicals	ISO 10545-13	GLA	GLA	GLA
Chemical Resistance - Low Concentration of Acids & Bases	ISO 10545-13	GLA	GLA	GLA
Scratch Hardness	MOHS	7	5	NA
NOTES				

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.