

Roma Italian Porcelain

Cross & Vein: 12x24, 24x24, 2.7x3.1 Hexagon
Mosaic,12x12 Sheet Intreccio Mosaic, 2.5x24
Battiscopa




SHADE VARIATION

Vein Ivory



V2 - Slight Variation Clearly distinguishable differences in texture and/or pattern within similar colors.



WEAR CODE

Roma is rated (4) for all residential and light commercial applications. Roma Ivory Cross is rated (5) for all residential and commercial applications.





Vein Cream

PERFORMANCE DATA

Characteristics.



Results

	Characteristics.	Norms.	nesuits
	Water Absorption	ISO 10545-3	< 0.1%
	Abrasion Resistance	ISO 10545-7	4/5
	Breaking Strength	ISO 10545-4	≥ 35 N/mm2
ははなる	Dynamic Coefficient of Friction	AcuTest	≥ 0.42
	Frost Resistance	ISO 10545-12	Frost Proof
	Chemical Resistance - Household Chemicals	ISO 10545-13	A-HA-LA
	Chemical Resistance - Low Concentration of Acids	ISO 10545-13	A-HA-LA
	Scratch Hardness	MOHS	>6

Cross Grey



. . .



Notes:

Per ANSI standard A108.02,4.3.8.2; tiles longer than 15" should not be staggered more than 1/3 the length of the tile.

Dynamic Coefficient of Friction > 0.42.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representation only.

Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

