

Pennsylvania Blue



# Aextra 20

Tile Pavers


24x24

# TILE

AMERICA

## SHADE VARIATION

V1 - Uniform Appearance  
Differences among pieces from the same production run are minimal.




Pennsylvania Grey



## WEAR CODE

Rated for all residential and commercial applications.

Graustein



## PERFORMANCE DATA


THICKNESS 20 mm

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ASTM C373	≤ 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	5/5
Breaking Strength	ASTM C648	≥ 3000 lbs
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions	ASTM C499	Conforms
Facial Range of Thickness	ASTM C499	Conforms
Warpage (Diagonal)	ASTM C485	Conforms
Wedging	ASTM C502	Conforms
Frost Resistance	ASTM C1026	Frost Resistant
Scratch Hardness	MOHS	6


Wind



Gea



Titanio



### Notes:

Is is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.  
Always inspect materials prior to installations.  
Always mix 2-3 cartons at a time while installing to insure the best blend.

**STOCKED IN CT!**

Book An Appointment



www.tileamerica.com