

Bianco



Aglow


Italian Porcelain

4x12, 12x24, 2x2 Mosaics, ,
.8x12 Quarter Round Glossy

TILE AMERICA SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Aglow Bianco/Taupe 12x24 and Bianco 4x12 are rated 4 for residential and light commercial applications.
Aglow Grigio/Nero 12x24 and 4x12 and Taupe 4x12 are rated 3 for residential applications.

Grigio



PERFORMANCE DATA

THICKNESS 10 mm

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5%
Abrasion Resistance	ISO 10545-7	3 / 4
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	A/LA/HA
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	A/LA/HA
Resistance to Stains	ISO 10545-14	Min. Class 3
Crazing Resistance of Glazed Tiles	ISO 10545-11	Min. Class 3
Dynamic Coefficient of Friction	AcuTest	≥ 0.42

Notes:

Per ANSI standart A108.02,4.3.8.2, joints on tiles longer tan 15" should not be staggered more than 1/3 the length of the tile.
Always inspect materials prior to installations.
Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com

