

Bianco



Bambusa

Italian Porcelain

12x24, 12x24 Fascia, 24x24 Intarsio, 9.5x11 Hexagon,
12x12 Intreccio Mosaic & Losanga Mosaic

TILE AMERICA


SHADE VARIATION

Grigio



Clearly distinguishable differences in texture and/or pattern within similar colors.

V2 - Slight Variation



WEAR CODE

Rated for all residential and commercial applications.

Crema



PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	0.10 %
Abrasion Resistance (Glazed)	ISO 10545-7	4/5
Breaking Strength	ISO 10545-4	≥ 55 N/mm2
Dynamic Coefficient of Friction Wet	AcuTest	0.50
Dimensions	ISO 10545-2	Conforms
Chemical Resistance	ISO 10545-13	Conforms
Thermal Shock	ISO 10545-9	Conforms
Resistance to Stains	ISO 10545-14	Class 5
Frost Resistance	ISO 10545-12	Frost Resistant
Scratch Hardness	MOHS	8.5

Beige



Tortora



Wenge



Notes:

It is not recommended to stagger tiles longer than 18" more than 1/3 the length of the tile.
Always inspect materials prior to installations.
Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com