

Camel



Amendoa




Bosque Wood Look 775x36

TILE AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications. (i.e., restaurants, offices)

THICKNESS: 7.4 mm PERFORMANCE DATA Characteristics: Norms: **Results** Water Absorption C373-16 ≤ 5% PEI Abrasion Resistance (Glazed) C1027-09 3 **Breaking Strength** C648-04 ≥275Lbf Dynamic Coefficient of Friction Wet A326-3 ≥0.42 C1028 Wedging $\pm 0.5\%$ Frost Proof **Frost Resistance** C1026-13 Chemical Resistance C650-04 Class A Stain Resistance Class A C1378-04 Resistance to Stains C1378-04 Class A **MOHS Hardness** C1895-20 5

Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile.

Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only.

Variation in color and shading is to be expected. Final selection should be made from actual tile samples.



www.tileamerica.com

Book An