




























The timeless look of limestone is created through this luxurious Italian porcelain collection. Breton is available in six elegant colorways that boast monochromatic tonality accented by subtle colorful chips. Available in a mix of matte and polished finishes, and a variety of shapes and sizes, Breton brings a modern feel to a classic look.

SIZES:	COLOR					
	Fresh	Bloom	Street	Frame	Board	Glow
12x24 Matte & Polished						
24x24 Matte & Polished						
2x2 Mosaic						
4x4.5 Hexagon Mosaic						

BRETON

TECHNICAL INFORMATION

SHADE VARIATION



V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

All colors in matte: 5 - Walls + Residential / Commercial Floor Applications; Bloom/Fresh/Street Polished: 4 - Walls + Residential / Light Commercial Floor Applications; Glow Polished: 3 - Walls + Residential Floor Applications; Frame/Board Polished: 2 - Walls + Light Residential Floor Applications

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 % (Matte)
Abrasion Resistance	ISO 10545-7	5 (Matte)
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction	AcuTest	≥ 0.42 (Matte)
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. Class B
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Min. Class 3

NOTES

It is not recommended to stagger any tile longer than 18” more than 1/3 the length of the tile.
Always inspect materials prior to installation.
Always mix 2-3 cartons at a time while installing to insure the best blend.