

CALACATTA TILE

HEX


AMERICA

Spanish Porcelain
20.5x24

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example “that little bit of color” on one piece of tile may be the primary color on the next piece.



SILVER



GOLD



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications. (i.e., restaurants, offices)

PERFORMANCE DATA

THICKNESS: 9.40 mm

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	< 0.5%
Abrasion Resistance	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 1300 N
Dynamic Coefficient of Friction	AcuTest	> 0.70
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	Resistant
Scratch Hardness	MOHS	7
Resistance to Stains	ISO 10545-14	Min. Class 3

Notes:

Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

Book An Appointment



www.tileamerica.com