




Indulge in the exquisite allure of the Carlisle Glazed Porcelain series, a masterful creation from the heart of Italy that draws inspiration from the captivating Brazilian Tiffany quartzite. Available in four breathtaking colors - Alabaster, Greige, Silver, and Wintergreen - each shade embodies its own unique character, adding a touch of sophistication to any space. The series offers versatility with two distinct finishes: the timeless natural finish and the luxurious lappato finish, both available in the elegant sizes of 12x24 and 24x24. Whether you prefer a classic or contemporary aesthetic, Carlisle effortlessly caters to your design preferences. For those seeking a touch of artistic flair, Carlisle presents two captivating mosaics in a matte finish. The 2x3 staggered brick joint mosaic exudes a sense of dynamic movement, while the 3x3.5 hexagon mosaic adds a geometric charm to elevate your design vision.

SIZES:	COLOR			
	Alabaster	Silver	Greige	Wintergreen
24x24	 	 	 	 
12x24				
2x3 Mosaic				
3x3.5 Hexagon				

CARLISLE

TECHNICAL INFORMATION

SHADE VARIATION



V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example “that little bit of color” on one piece of tile may be the primary color on the next piece.

WEAR CODE

Lappato: Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications. (i.e., restaurants, offices)

Matte: Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use. (i.e., Shopping Malls, Hospitals)

THICKNESS

9.0mm Thickness

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	> 40 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	≥0.42 (Matte)
Thickness Dimension	ISO 10545-2	Compliant
Frost Resistance	ISO 10545-12	Frost Proof
Resistance to Stains	ISO 10545-14	Min Class 3
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. UB
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Min. UB

NOTES

It is not recommended to stagger any tile longer than 18” more than 1/3 the length of the tile.
 Always inspect materials prior to installation.
 Always mix 2-3 cartons at a time while installing to insure the best blend.
 We recommend a minimum grout joint of no less than 3/16” for pressed tiles.