

Carrara

Brazilian Porcelain

Matte & Polished: .7x1 Herringbone Mosaics, 2x3
Hexagon Mosaics 3x8 Picket Mosaics, 12x24, 24x24,
24x48

TILE

AMERICA


Carrara



SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications.
Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: From 9.5 mm to 11 mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.5%
Abrasion Resistance	ASTM C1027	4
Breaking Strength	ASTM C648	275
Dynamic Coefficient of Friction Wet	AcuTest	≥0.42 (Matte); 0.30 (Polished)
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Class C
Scratch Hardness	MOHS	5 (Matte); 4 (Polished)

Notes:

Per ANSI standard A108.02, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile.

9.5mm Thickness: 12x24 Matte, 24x24 Matte and Polished

10.5mm Thickness: 12x24 Polished

11mm Thickness: 24x48 Matte and Polished, .7x1.4 Matte and Polished, 2x3 Matte and Polished and 3x8 Matte and Polished

Book An
Appointment



www.tileamerica.com