

Classic

American Porcelain
2x2 Mosaic, 12x24, 3x12 Bullnose

TILE


AMERICA

SHADE VARIATION

Statuarietto



V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: 8.00 mm

Cremino



Characteristics:	Norms:	Results
Water Absorption	C373	≤ 0.1
Abrasion Resistance (Glazed)	C1243	< 150 mm ³
Breaking Strength	C648	≥ 350 lbf
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Static Coefficient of Friction Wet	C1028	≥ 0.62
Chemical Resistance	C650	Unaffected
Warpage (Diagonal)	C485	≤ 0.40%
Wedging	C502	≤ 0.25%
Frost Resistance	C1026	Frost Resistant
Scratch Hardness	MOHS	7
Notes:		

Bardiglietto



Per ANSI standard A108.02 4.3.8.2, joints on 12x24 should not be staggered more than 1/3 the length of the tile.
Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only.
Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

Book An Appointment

