









Introducing Cocoon Italian porcelain tiles - a captivating reinterpretation of the classic wood plank look, adorned with a graceful reflection of Europe's most cherished Oaks. Immerse yourself in the beauty of these color body porcelain tiles, meticulously crafted to embody the essence of Eastern European Oak, renowned for its historical significance in wine barrel craftsmanship. Experience the natural allure of wood tones brought to life in an impressive 8" x 48" rectified plank tile format, available in five enchanting low-variation colors: indulge in the warm embrace of three exquisite Beige options ('Bliss', 'Glee', and 'Joy'), or savor the sophistication of a Light Brown tile ('Ease') and a rich Brown tile ('Peace'). Enhance your space with artistic flair, as Cocoon offers delightful decorative tile alternatives, including a stunning 3" x 18" Chevron pattern, available in the captivating hues of 'Ease', 'Glee,' and 'Joy.' Embracing Versatility: Cocoon Italian porcelain tiles are meticulously engineered to excel in any setting, making them ideal for all applications, ensuring your creative visions can be brought to life with ease and confidence.

SIZES:	COLOR				
8x48	Bliss 	Glee 	Joy 	Ease 	Peace 
3x18 Chevron	Glee 		Joy 		Ease 

COCOON

TECHNICAL INFORMATION

SHADE VARIATION



V2 - Slight Variation  
Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use. (i.e., Shopping Malls, Hospitals)

THICKNESS

Thickness: 9mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.1 %
Deep Abrasion	ISO 10545-6	Conforms
Breaking Strength	ISO 10545-4	Conforms
Dynamic Coefficient of Friction	AcuTest	> 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	Resistant
Resistance to Stains	ISO 10545-14	Cleanable
Thermal Shock Resistance	ISO 10545-9	Resistant

NOTES

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.  
Always inspect materials prior to installation.  
Minimum Recommended Grout Joint for Non-Rectified 3x18 tiles is no less than 3/16".  
Minimum Recommended Grout Joint for Rectified 8x48 tiles is no less than 1/8".  
Always mix 2-3 cartons at a time while installing to insure the best blend.