



Cocoon

Wood Look


8x48, 3x48 (Glee, Joy, Ease)

TILE

AMERICA

SHADE VARIATION

V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

PERFORMANCE DATA

THICKNESS: 9.00 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.1 %
Deep Abrasion	ISO 10545-6	Conforms
Breaking Strength	ISO 10545-4	Conforms
Dynamic Coefficient of Friction	AcuTest	> 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	Resistant
Resistance to Stains	ISO 10545-14	Cleanable
Thermal Shock Resistance	ISO 10545-9	Resistant

Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15” should not be staggered more than 1/3 the length of the tile.
Minimum Recommended Grout Joint for Non-Rectified 3x18 tiles is no less than 3/16”.
Minimum Recommended Grout Joint for Rectified 8x48 tiles is no less than 1/8”.
Dynamic Coefficient of Friction (DCOF) is > 0.42 Wet.

