



Easel is the series you've been waiting for. This gorgeous replication of limestone recreated in durable Italian glazed porcelain has something for everyone. Easel is available in four essential colors: White, Sand, Greige, Light Grey. Each color is available in a plain field tile in both 4x12 and 12x24, along with 2x2 mosaics and trim. In addition there are three exciting and unique finishes in 12x24 per color: Triangles and Chesterfield (fabric weave) are semi-polished Lappato designs and Ribbed is a 3- dimensional linear glazed tile. 3x24 trim accompanies the series.

SIZE	COLOR			
	White	Sand	Light Grey	Greige
12 x 24				
12 x 24 Ribbed				
12 x 24 Chesterfield				
12 x 24 Triangles				
2 x 2 Mosaic				
4 x 12				




# EASEL TECHNICAL INFORMATION

## TILE SIZE

NOMINAL	SHAPE	MATERIAL	THICKNESS
12 x 24		PORCELAIN	9.5 MM
4 x 12		PORCELAIN	9.5 MM
2 x 2 Mosaic		PORCELAIN	9.5 MM

## SHADE VARIATION

V3 - Moderate Variation



While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

## WEAR CODE

White / Sand: 5

Rated for all residential and commercial applications.

Light Grey / Greige: 4

Rated for all residential and light commercial applications.

## APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✓	✓	✓
WALLS / BACKSPLASH	✓	✓	✓
POOL DECKING			
EXTERNAL USE - FROST PROOF	✓	✓	✓

## PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5
Abrasion Resistance (Glazed)	ISO 10545-7	4/5
Breaking Strength	ISO 10545-4	≥ 35 N/mm <sup>2</sup>
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions	ISO 10545-2	Conforms
Deep Abrasion	ISO 10545-6	≤ 175 mm <sup>3</sup>
Chemical Resistance	ISO 10545-12	Conforms
Thermal Shock Resistance	ISO 10545-9	Conforms
Frost Resistance	ISO 10545-12	Frost Resistant
Resistance to Stains	ISO 10545-14	Class 5

## NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.