



The porcelain series Foundry26 features the latest aesthetic trend of the new metal effect. Available in four stunning colors: Zinc, Alloy, Oxide and Rail. Made in America, inspired by Italian design. A bullnose trim is available.






FOUNDRY26

TECHNICAL INFORMATION

SHADE VARIATION



V2 - Slight Variation Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

5 - Rated for all residential and commercial applications.

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	C373	≤ 0.5%
PEI Abrasion Resistance (Glazed)	C1027	NA
Breaking Strength	C648	≥400 lbs
Dynamic Coefficient of Friction Wet	AcuTest	0.55
Dimensions Range	C499	.5% (+/- 2 mm)
Facial Range of Thickness	C499	≤ 0.5% (+/- 2 mm)
Wedging	C502	≤ 0.5% (+/- 2 mm)
Frost Resistance	C1026	Frost Proof
Chemical Resistance	C650	Unaffected
Scratch Hardness	MOHS	7

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected.

Final selection should be made from actual tile samples.