




Go Big is an exciting Outlet large-format glazed porcelain series from Brazil that offers the look of softly veined sandstone. This 24x24 pressed tile is available in three warm colorways: Shell (ivory), Marfim (beige), and Warm Greige (brown). Available as a value-based series, Go Big is on trend not only in size but with its warm tones.

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15” should not be staggered more than 1/3 the length of the tile.

COLOR	SIZES:			
24x24	<table border="0"> <tr> <td data-bbox="185 1444 646 1942"> <p data-bbox="185 1444 266 1472">Shell</p>  </td> <td data-bbox="662 1444 1123 1942"> <p data-bbox="672 1444 889 1472">Warm Greige</p>  </td> <td data-bbox="1140 1444 1594 1942"> <p data-bbox="1156 1444 1273 1472">Marfim</p>  </td> </tr> </table>	<p data-bbox="185 1444 266 1472">Shell</p> 	<p data-bbox="672 1444 889 1472">Warm Greige</p> 	<p data-bbox="1156 1444 1273 1472">Marfim</p> 
<p data-bbox="185 1444 266 1472">Shell</p> 	<p data-bbox="672 1444 889 1472">Warm Greige</p> 	<p data-bbox="1156 1444 1273 1472">Marfim</p> 		

SHADE VARIATION



V2 - Slight Variation

Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications. (i.e., restaurants, offices)

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ASTM C373	≤ 0.5 %
Abrasion Resistance	ASTM C1027	4
Breaking Strength	ASTM C648	≥ 400 lbs
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Class E
Scratch Hardness	MOHS	5

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.
Always inspect materials prior to installation.
Always mix 2-3 cartons at a time while installing to insure the best blend.