




The Marmi series is comprised of Italian glazed porcelain tiles that replicate five gorgeous various marbles. Each of the stunning colors: Marquina Black, Marquina White, Arabescato, Statuario Superiore, and Cenerino comes in a vast range of sizes and finishes.

Note: Black Polished is rated (2) for light residential applications. Black Matte and Cenerino Polished are rated (3) for residential applications. All other colors/finishes are rated (4) for residential and light commercial applications.

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile.

SIZES:	COLOR				
	Marquina White	Statuario Superiore	Arabescato	Cenerino	Marquina Black
12x24 Rectified Polished & Matte					
24x48 Rectified Polished & Matte					
24x24 Rectified Polished & Matte					
4x4.5 Hexagon Matte Mosaic					
2x2 Matte Mosaic					
4x24 Rectified Matte					
1x3 Herringbone Matte Mosaic	Images Coming Soon				

SHADE VARIATION



V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

Black Polished: 2 - Walls and Light Residential Floor Applications
 Black Matte and Cenerino Polished: 3 - Walls and Residential Floor Applications
 All other colors/finishes: 4 - Walls and Residential and Light Commercial Floor Applications

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5%
Abrasion Resistance	ISO 10545-7	2 / 3 / 4
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction	AcuTest	≥ 0.42 (Matte)
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Min Class 3
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	Min Class 3
Resistance to Stains	ISO 10545-14	Min Class 3
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.
 Always inspect materials prior to installation.
 Always mix 2-3 cartons at a time while installing to insure the best blend.

DCOF of Honed is > 0.45 Wet.
 Minimum Recommended Grout Joint for Rectified tiles is no less than 1/8".