



























The Martini series is a vibrant collection of 2x6 glazed porcelain tiles from Europe. This fun line is comprised of 8 colors and 3 exciting finishes per colorway. Martini is sure to bring any project to the next level with its textural or visual design elements. The 3 finishes are glossy (satin), matte, or stripes (3D- satin), all are available in 8 colors: Pure White, Sand, Mint, Tiffany, Green, Grey, Denim, and Terracotta. The 8 colors are available in coordinating matte and glossy quarter rounds.


Note: Martini Stripes is rated (1) for walls only, Martini light colors is rated (4) for for all residential and commercial applications and Martini dark colors is rated (3) for residential applications.

SIZES:	COLOR
2x6 Glossy	 Pure White  Sand  Grey  Mint  Tiffany  Green
	 Denim  Terracotta
2x6 Matte	 Pure White  Sand  Grey  Mint  Tiffany  Green
	 Denim  Terracotta
2x6 Stripes	 Pure White  Sand  Grey  Mint  Tiffany  Green
	 Denim  Terracotta

MARTINI

TECHNICAL INFORMATION

SHADE VARIATION



V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example “that little bit of color” on one piece of tile may be the primary color on the next piece.

WEAR CODE

Martini Stripes is rated (1) for walls only.

Martini light colors is rated (4) for for all residential and commercial applications and

Martini dark colors is rated (3) for residential applications.

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5%
Abrasion Resistance	ISO 10545-7	3 / 4
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction	AcuTest	> 0.42 (Matte)
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance Household Chemicals	ISO 10545-13	GA/GLA
Chemical Resistance Low Concentration of Acids	ISO 10545-13	GA/GLA
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Conforms
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

NOTES

It is not recommended to stagger any tile longer than 18” more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

Dynamic Coefficient of Friction (DCOF) for MATTE finish is > 0.42 Wet. Minimum

Recommended Grout Joint for Non-Rectified tiles is no less than 3/16”.