




















Oahu is a glazed porcelain series from Italy that has the look and subtle texture of blended strips of wood. Available in four striking blends: Ivory, Beige, Honey, and Sky Blue, each of which works well with the warmer color trends that are being seen among design trends. All colors come in a 12x24 rectified, a 9.5x11 Hexagon, 12x12 Intreccio Mosaic, 10x12 Hexagon Mosaic, and a matching battiscopa.

SIZES:	COLOR			
	Sky Blue	Ivory	Beige	Honey
12x24 Porcelain Rectified				
9.5x11 Hexagon				
12x12 Intreccio Mosaic				
10x12 Hexagon Mosaic				

OAHU

TECHNICAL INFORMATION

SHADE VARIATION



V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications. (i.e., restaurants, offices)

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.1 %
Abrasion Resistance	ISO 10545-7	4
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Dynamic Coefficient of Friction Wet	DCOF	> 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance Household Chemicals	ISO 10545-13	A-LA-HA
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resists

NOTES

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.
Always inspect materials prior to installation.
Always mix 2-3 cartons at a time while installing to insure the best blend.
Minimum Recommended Grout Joint for Rectified tiles is no less than 1/8.