

















PROVENCE





Tile America brings you Provenca, a stunning Italian porcelain tile series that replicates the beauty and elegance of French limestone. This is a classic stone look which is available in three sizes and four colors: Ivory, Cloud (grey), Coal (black) and Ecrú (taupe). mosaics and bullnose trim complete the package of this updated sensation.

Provenca offers multiple design options with 3 modular rectified field tile sizes. The Coal color is reminiscent of Belgian Blue stone. A matching Battiscopa is available to complete the collection.

SIZE	COLOR			
	Coal	Ivory	Ecrú	Cloud
24 x 24				
12 x 24				
12 x 12				
2 x 2 Mosaic				

PROVENCE TECHNICAL INFORMATION


TILE SIZE

NOMINAL	SHAPE	MATERIAL	THICKNESS
24 x 24		PORCELAIN	10 MM
12 x 24		PORCELAIN	10 MM
12 x 12		PORCELAIN	10 MM
2 x 2 Mosaic		PORCELAIN	10 MM

WEAR CODE

All Sizes: 4
 Rated for all residential and light commercial applications.

SHADE VARIATION



V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✓	✓	
WALLS / BACKSPLASH	✓	✓	✓
POOL DECKING	✓	✓	
EXTERNAL USE - FROST PROOF	✓	✓	

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.05 %
Abrasion Resistance (Glazed)	ISO 10545-7	4/5
Breaking Strength	ISO 10545-4	≥ 45 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Frost Resistance	ISO 10545-12	Frost Resistant
Chemical Resistance	ISO 10545-13	Conforms
Scratch Hardness	MOHS	9
Resistance to Stains	ISO 10545-14	Class 5

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.