

QUARTZ ESSENCE



This beautiful Italian porcelain series spotlights vein patterns, color variation, and a mix of matte and reflective surfaces to bring the true essence of Alpine quartzite. Available in five stunning colors: White (Flake), Beige (Nest), Light Grey (Rocky), Dark Grey (Burnt) and Brown/Green mix (Wild). This series is available in rectified 12x24, 4x24, 2x2 mosaics, and coordinating trim.


Per ANSI standard A108.02,4.3.8.2, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile.

SIZES:	COLOR				
	Flake	Rocky	Burnt	Nest	Wild
12x24					
4x24					
2x2 Mosaic					


QUARTZ ESSENCE

TECHNICAL INFORMATION

SHADE VARIATION



V3 - Moderate Variation
While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use. (i.e., Shopping Malls, Hospitals)

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.1 %
Abrasion Resistance	ISO 10545-7	5
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance Low Concentration of Acids	ISO 10545-13	Resistant
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Cleanable

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.
Always inspect materials prior to installation.
Always mix 2-3 cartons at a time while installing to insure the best blend.

Dynamic Coefficient of Friction is greater than or equal to 0.45 wet.
Minimum recommended grout joint for this rectified tile series is 1/8".