



Style offers a modern, minimalist linear look. This Made in America rectified porcelain plank series is available in four subtle colors: Pure (Ivory), Lively (Grey), Elegant (Taupe), and Rich (Brown). Additional sizes and trims are available to complete the look.


**Per ANSI standard A108.02, 4.3.82, joints on tiles longer than 15” should not be staggered more than 1/3 the length of the tile.**

SIZES:	COLOR			
12x24	Pure	Lively	Elegant	Rich
2x2 Mosaics				

STYLE

TECHNICAL INFORMATION

SHADE VARIATION



V2 - Slight Variation

Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use. (i.e., Shopping Malls, Hospitals)

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ASTM C373	≤ 0.5 %
Breaking Strength	ASTM C648	≥ 400 lbs
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Thickness Dimension	ASTM C499	In Accordance
Facial Dimension	ASTM C499	In Accordance
Warpage Diagonal	ASTM C485	In Accordance
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Unaffected
Scratch Hardness	MOHS	6
Wedging ASTM	C502	In Accordance

NOTES

Dynamic Coefficient of Friction (DCOF) is greater than or equal to 0.42 Wet. Minimum Recommended Grout Joint for Rectified tiles is no less than 1/8".

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to insure the best blend.