














# TAPESTRY WOOD



Tapestry Wood is a Spanish tile collection that evokes the look of wood planks and wooden parquet styles. This porcelain series is made up of 8x48 planks and 8x8 patterned field tiles. The planks have a modern, sleek appearance with a subtle hand-carved surface. In addition to the four main colors, the plank is available in four unique patterns. Each of the plank's four wood colors is incorporated into the 8x8 designs to create a fully interchangeable and custom look.


**Per ANSI standard A108.02, 4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile.**

SIZES:	COLOR
8x48 Rectified	<div style="display: flex; flex-direction: column; align-items: center;"> <div style="display: flex; align-items: center; width: 100%;"> <div style="width: 15%; text-align: center;"><b>Ice</b></div>  </div> <div style="display: flex; align-items: center; width: 100%; margin-top: 10px;"> <div style="width: 15%; text-align: center;"><b>Smoke</b></div>  </div> <div style="display: flex; align-items: center; width: 100%; margin-top: 10px;"> <div style="width: 15%; text-align: center;"><b>Moka</b></div>  </div> <div style="display: flex; align-items: center; width: 100%; margin-top: 10px;"> <div style="width: 15%; text-align: center;"><b>Malt</b></div>  </div> </div>
8x8	<div style="display: grid; grid-template-columns: repeat(6, 1fr); gap: 5px;"> <div style="display: flex; align-items: center;"> <div style="width: 15%; text-align: center;"><b>Flor Moka</b></div>  </div> <div style="display: flex; align-items: center;"> <div style="width: 15%; text-align: center;"><b>Flor Colors</b></div>  </div> <div style="display: flex; align-items: center;"> <div style="width: 15%; text-align: center;"><b>Flor Smoke</b></div>  </div> <div style="display: flex; align-items: center;"> <div style="width: 15%; text-align: center;"><b>Medi Moka</b></div>  </div> <div style="display: flex; align-items: center;"> <div style="width: 15%; text-align: center;"><b>Medi Smoke</b></div>  </div> <div style="display: flex; align-items: center;"> <div style="width: 15%; text-align: center;"><b>Lis Moka</b></div>  </div> <div style="display: flex; align-items: center;"> <div style="width: 15%; text-align: center;"><b>Lis Smoke</b></div>  </div> <div style="display: flex; align-items: center;"> <div style="width: 15%; text-align: center;"><b>Park Moka</b></div>  </div> <div style="display: flex; align-items: center;"> <div style="width: 15%; text-align: center;"><b>Park Smoke</b></div>  </div> </div>

TAPESTRY WOOD

TECHNICAL INFORMATION

SHADE VARIATION



V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example “that little bit of color” on one piece of tile may be the primary color on the next piece.

WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use. (i.e., Shopping Malls, Hospitals), Class 3 Residential Applications. Suitable for all residential applications.

Minimum Recommended Grout Joint for **PRESSED** tiles is no less than 3/16”.  
 Minimum Recommended Grout Joint for **RECTIFIED** tiles is no less than 1/8”.

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5%
Deep Abrasion	ISO 10545-6	<130 mm <sup>3</sup> (8x48)
Abrasion Resistance	ISO 10545-7	3 / 4 / 5
Breaking Strength (8x8)	ISO 10545-4	≥ 52 N/mm <sup>2</sup> (8x48); ≥ 46 N/mm <sup>2</sup>
Dynamic Coefficient of Friction	AcuTest	≥ 0.60
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance		
Household Chemicals	ISO 10545-13	A/LA/HA
Chemical Resistance		
Low Concentration of Acids	ISO 10545-13	A/LA/HA
Resistance to Stains	ISO 10545-14	Class 5

NOTES

- It is not recommended to stagger any tile longer than 18” more than 1/3 the length of the tile.
- Always inspect materials prior to installation.
- Always mix 2-3 cartons at a time while installing to insure the best blend.