





Take a step back in time, but with the updated colors of today. Terra is reminiscent of the worn stone floors found across the Mediterranean, think aged Tuscan travertine. With its tumbled edges and a blend of classic and modern, this Italian glazed porcelain has the look of tumbled stone with natural variation and character that has been aged by time. Available in 4 colors: Byblos (Taupe), Erice (Grey), Dor (Beige), and Menfi (Black), Terra comes with a clean edge and is available in four modular sizes that can be used separately or in a variety of patterns. To complete the look, Terra has a matching trim piece. Terra Dor is rated (5) for all residential and commercial applications while Byblos, Erice, and Menfi are rated (4) for residential and light commercial applications.

| SIZES: | COLOR | | | |
|----------------|---|---|--|---|
| | Dor | Erice | Byblos | Menfi |
| 8x8 |  |  |  |  |
| 8x16 16x24 |  |  |  |  |
| 16x16 |  |  |  |  |
| 2x2 Mosaics |  |  |  |  |

TERRA

TECHNICAL INFORMATION

SHADE VARIATION



V4 - Random Variation

Random Color differences from tile to tile, so that one tile may have totally different colors from that of other tiles. Thus the final installation will be unique.

WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use. (i.e., Shopping Malls, Hospitals), Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications. (i.e., restaurants, offices)

PERFORMANCE DATA

| CHARACTERISTIC | NORMS | RESULTS |
|------------------------------------|--------------|------------------------|
| Water Absorption | ISO 10545-3 | ≤ 0.2 % |
| Abrasion Resistance | ISO 10545-7 | 4 / 5 |
| Breaking Strength | ISO 10545-4 | ≥ 35 N/mm ² |
| Dynamic Coefficient of Friction | AcuTest | 0.68 |
| Dimensions Range | ISO 10545-2 | Conforms |
| Frost Resistance | ISO 10545-12 | Frost Proof |
| Chemical Resistance | | |
| Household Chemicals | ISO 10545-13 | GA/GLA/GHA |
| Chemical Resistance | | |
| Low Concentration of Acids | ISO 10545-13 | GA/GLA/GHA |
| Thermal Shock Resistance | ISO 10545-9 | Resistant |
| Resistance to Stains | ISO 10545-14 | Class 5 |
| Crazing Resistance of Glazed Tiles | ISO 10545-11 | Resistant |

NOTES

- It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.
- Always inspect materials prior to installation.
- Always mix 2-3 cartons at a time while installing to insure the best blend.
- Dynamic Coefficient of Friction for Terra is greater than or equal to 0.43 wet.
- Minimum recommended grout joint for this Rectified tile series is 1/8", but when mixing sizes larger joints may be necessary.