www.tileamerica.com

$\top \mid \mathsf{L} \vDash \diamondsuit \land \mathsf{A} \bowtie \mathsf{R} \upharpoonright \mathsf{C} \land \mathsf{A}^{\circ}$



The Tiburon series is a classic floor and wall collection with inspirations from traditional vein-cut travertine in ceramic and porcelain. Tiburon offers many sizes, styles, and finishes among the collection and is available in four soft tones: White, Light Grey, Silver, and Beige. Note: Beige, Light Grey, and White are rated for all residential and commercial uses. Silver is rated for all residential and light commercial applications. A matching bullnose completes the collection.


SIZES:	COLOR			
2x2 Mosaic	Beige	Light Grey	Silver	White
10x22 Glossy Wall				
10x22 Wave Wall				
12x24				
12x12				
4x12			And Service	

$\top \mid \mathsf{L} \vDash \diamondsuit \land \mathsf{A} \land \mathsf{M} \vDash \mathsf{R} \upharpoonright \mathsf{C} \land \mathsf{A}^{\circ}$

TIBURON

TECHNICAL INFORMATION

SHADE VARIATION



V2 - Slight Variation Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

10x22 / Bullnose: 1 - Wall Applications Only. Silver: 4 - Walls + Residential / Light Commercial Floor Applications. Beige, Light Grey, White: 5 - Walls + Residential / Commercial Floor Applications

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Abrasion Resistance	ASTM C1027	4/5
Breaking Strength	ASTM C648	≥ 140 kN
Bond Strength	ASTM C482	≥ 50 psi
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Thickness Dimension	ASTM C499	In accordance
Facial Dimension	ASTM C499	In accordance
Warpage Diagonal	ASTM C485	In accordance
Wedging	ASTM C502	In accordance
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	GL: GA, GLA

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.