




























Topography is an Italian porcelain series that replicates the look of natural stone. This textured collection is offered in two field tile sizes: 4x24, and 12x24, as well as three different mosaics patterns (square, hexagon, and herringbone). Each size is available in Grey, Nero, Taupe, and White. Trim sizes are available to round out the full collection. The minimum recommended grout joint for this series is 1/8" and colors: Grey, Nero, and Taupe are rated for all residential and light commercial uses with the White rated for all residential and commercial uses.

SIZE	COLOR			
	White	Taupe	Grey	Black
12 x 24				
4 x 24				
2 x 2 Mosaic				
1 x 3 Herringbone				
4 x 4.5 Hexagon				


TOPOGRAPHY TECHNICAL INFORMATION

TILE SIZE

NOMINAL	SHAPE	MATERIAL	THICKNESS
12 x 24		PORCELAIN	9 MM
4 x 12		PORCELAIN	9 MM
2 x 2 Mosaic		PORCELAIN	9 MM
Herringbone		PORCELAIN	9 MM
Hexagon		PORCELAIN	9 MM

SHADE VARIATION

V3 - Moderate Variation



While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example “that little bit of color” on one piece of tile may be the primary color on the next piece.

WEAR CODE

White: 5
Rated for all residential and commercial applications.

All Other Colors: 4
Rated for all residential and light commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✓	✓	✓
WALLS / BACKSPLASH	✓	✓	✓
POOL DECKING	✓	✓	
EXTERNAL USE - FROST PROOF	✓	✓	

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	4/5
Breaking Strength	ISO 10545-4	≥ 35 N/mm2
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Resistant
Chemical Resistance	ISO 10545-13	Conforms
Thermal Shock Resistance	ISO 10545-9	Conforms
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

NOTES

- It is not recommended to stagger any tile longer than 18” more than 1/3 the length of the tile.
- Always inspect materials prior to installation.
- Always mix 2-3 cartons at a time while installing to insure the best blend.