


Elevate your design vision with the Villa Ceramic Tile collection from Brazil. Unleash your creativity with these 4x16 tiles, boasting precise straight edges and a subtly undulating surface that mimics the charm of handmade craftsmanship. Villa embodies exquisite artistry and offers a palette of eight enchanting shades: Off-White, Gris, Green, Agave, Cotto, Glacial, Marine, and Carbon. Discover the possibilities and let your designs flourish with Villa.

| SIZES: | COLOR | | | | | | | |
|--------|-----------|------|---------|--------|-------|--------|-------|--------|
| 4X16 | Off White | Gris | Glacial | Marine | Green | Agave | Cotto | Carbon |
| | | | | | | * - 10 | | 0.002 |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | 100 |
| | | | | | | | [] | 44 |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |



TECHNICAL INFORMATION

SHADE VARIATION



V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

Class 1 Rated for wall application only

THICKNESS

7 mm Thickness.

PERFORMANCE DATA

| CHARACTERISTIC | NORMS | RESULTS | |
|---------------------|------------|-----------|--|
| Water Absorption | ASTM C373 | ≤ 20 % | |
| Abrasion Resistance | ASTM C1027 | 1 | |
| Breaking Strength | ASTM C648 | ≥ 125 lbs | |
| Chemical Resistance | ASTM C650 | Class A | |
| Scratch Hardness | MOHS | 4 | |

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

We recommend a minimum grout joint of no less than 3/16" for pressed tiles.