



Whisper is a modern porcelain series that offers a wood-look plank style. This collection is designed in Italy and produced in the United States. Whisper is suitable for all residential and commercial applications.

| SIZE   | COLOR   |  |
|--------|---|--|
|        | Ash   | Sand   |
| 8 x 40 | THE POLICE OF THE PARTY OF THE | A STATE OF THE PARTY OF THE PAR |
|        |   |  |
|        | Forest  |  |
|        | THE RESERVE OF THE PARTY NAMED IN   |  |
|        |   |  |
|        | Breeze  |  |
|        |   |  |
|        |   |  |
|        |   |  |



# WHISPER TECHNICAL INFORMATION

# TILE SIZE

| NOMINAL | SHAPE | MATERIAL  | THICKNESS |
|---------|-------|-----------|-----------|
| 8 x 40  |       | PORCELAIN | 9 MM      |

# SHADE VARIATION



V2 - Slight Variation

Clearly distinguishable differences in texture and/or pattern within similar colors.

#### **APPLICATIONS**

|                               | RESIDENTIAL | LIGHT<br>COMMERCIAL | COMMERCIAL |
|-------------------------------|-------------|---------------------|------------|
| FIOORS                        | ✓           | ✓                   | ✓          |
| WALLS /<br>BACKSPLASH         | ✓           | ✓                   | ✓          |
| POOL DECKING                  | ✓           | ✓                   |            |
| EXTERNAL USE<br>- FROST PROOF | <b>√</b>    | <b>✓</b>            |            |

# WEAR CODE

8 x40: 5 Rated for all residential and commercial applications.

# PERFORMANCE DATA

| CHARACTERISTIC                      | NORMS   | RESULTS         |
|-------------------------------------|---------|-----------------|
| Water Absorption                    | C373    | ≤ 0.5 %         |
| Chemical Resistance                 | C650    | Unaffected      |
| Breaking Strength                   | C648    | ≥ 400 lbs       |
| Dynamic Coefficient of Friction Wet | AcuTest | ≥ 0.42          |
| Dimensions                          | C499    | Conforms        |
| Facial Range of Thickness           | C499    | Conforms        |
| Warpage (Diagonal)                  | C485    | Conforms        |
| Wedging                             | C502    | Conforms        |
| Frost Resistance                    | C1026   | Frost Resistant |
| Scratch Hardness                    | MOHS    | 6               |

# **NOTES**

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.