

BIANCO

# BAMBUSA TILE

## AMERICA

Italian Porcelain


12x24, 12x24 Fascia, 24x24 Intarsio, 9.5x11 Hexagon,  
1.5x2 Intreccio Mosaic & Losanga Mosaic

## SHADE VARIATION

GRIGIO



V2 - Slight Variation

Clearly distinguishable differences in texture and/or pattern  
within similar colors.

CREMA



## PERFORMANCE DATA

Thickness: 10mm

CHARACTERISTIC	NORMS	RESULTS
Abrasion Resistance	ISO 10545-7	4
Breaking Strength	ISO 10545-4	$\geq 55$ N/mm <sup>2</sup>
Water Absorption	ISO 10545-3	0.10%
Dynamic Coefficient of Friction	AcuTest	0.5
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	A-LA-HA
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	A-LA-HA
Scratch Hardness	MOHS	8.5
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Class 5

Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Minimum Grout Joint Recommendation: 3/16" for 8x8 & Hexagon; 1/8" for all other sizes. Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

BEIGE



TORTORA



WENGE



Book An  
Appointment



www.tileamerica.com