WHITE

CALGARY


Stone Look 12x24, 4x12, 2x3 Muretto Mosaic, Bullnose



SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

THICKNESS: 9mm

Frost Proof

Min. Class B

Min. Class 3

White: Class 5 Suitable for all Residential and Commercial Application.

Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

Dark: Class 3 Residential Applications. Suitable for all residential applications.

All other colors: Class 4 All Residential and Light Commercial Applications.

Class 4 tiles may be used in all residential areas and light commercial applications.



GREY

PERFORMANCE DATA
Characteristics:

EMERALD

DARK

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	< 0.5%
Abrasion Resistance	ISO 10545-7	3/4/5
Breaking Strength	ISO 10545-4	≥ 35 N/mm2
Dynamic Coefficient of Friction	AcuTest	> 0.50

ISO 10545-12

ISO 10545-13

ISO 10545-14

Notes:

Frost Resistance

Chemical Resistance

Resistance to Stains

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.



www.tileamerica.com