WHITE

**GREY** 

**BEIGE** 


## **CALGARY**

Stone Look 4x12, 12x12, 12x24, 12x36, 24x24, 24x48, 2x3 Muretto Mosaic, Bullnose



SHADE VARIATION

V3 - Moderate Variation While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the



## WEAR CODE

White: Class 5 Suitable for all Residential and Commercial Application.

Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

Dark: Class 3 Residential Applications. Suitable for all residential applications.

All other colors: Class 4 All Residential and Light Commercial Applications.

Class 4 tiles may be used in all residential areas and light commercial applications.

primary color on the next piece.



**EMERALD** 

PERFORMANCE DATA

THICKNESS: 9mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	< 0.5%
Abrasion Resistance	ISO 10545-7	3/4/5
Breaking Strength	ISO 10545-4	≥ 35 N/mm2
Dynamic Coefficient of Friction	AcuTest	> 0.50
Dynamic Coefficient of Friction  Frost Resistance	AcuTest ISO 10545-12	> 0.50 Frost Proof
·		

MINT

**PINK** 

BLUE

Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.



www.tileamerica.com