


CASTLE COTTO

Spanish Porcelain
13x13

TILE AMERICA

SHADE VARIATION

V2 - Slight Variation
Clearly distinguishable differences in texture and/or
pattern within similar colors.



WEAR CODE

Class 4 All Residential and Light Commercial Applications.
Class 4 tiles may be used in all residential areas and light
commercial applications.

PERFORMANCE DATA

THICKNESS: From 8.00 mm

Characteristic:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5%
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	> 2600 N
Dynamic Coefficient of Friction Wet	C1028	Teja = 0.62 Gris = 0.64
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GLA/GHA
Chemical Resistance - Low Concentration of Acids & Bases	ISO 10545-13	GLA/GHA
Thermal Shock Resistance	ISO 10545-9	Passes
Resistance to Stains	ISO 10545-14	Class 5

GRIS



TEJA



Notes:

Coefficient of Friction of greater or equal to .64 WET.
The results are based on ASTM C 1028 test. Results can vary from tile to tile, and
dye lot to dye lot.
Always inspect materials prior to installations.
Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An
Appointment



Stocked in CT!

www.tileamerica.com