

CALACATTA
ORO



BIANCO
CARRARA



TRAVERTINO
GRIGIO



CLASSIC 2.0 TILE

American Porcelain


2x2 Mosaic, 12x12, 12x24, 3x12 Bullnose

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications.
Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: 8.00 mm

Characteristics:	Norms:	Results
Water Absorption	C373	≤ 0.1
Abrasion Resistance (Glazed)	C1243	< 150 mm ³
Breaking Strength	C648	≥ 350 lbf
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Static Coefficient of Friction Wet	C1028	≥ 0.62
Chemical Resistance	C650	Unaffected
Warpage (Diagonal)	C485	≤ 0.40%
Wedging	C502	≤ 0.25%
Frost Resistance	C1026	Frost Resistant
Scratch Hardness	MOHS	7

Notes:

Per ANSI standard A108.02,4.3.8.2, tiles longer than 15" should not be staggered more than 1/3 the length of the tile.

Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representation only.

Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

Book An
Appointment



www.tileamerica.com