

LIGHT



IKONITE

Stone Look

12x24, 24x24, 24x48, Hexagon Mosaics, 4x24
Bullnose


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WALNUT



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: 8mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.5 %
Abrasion Resistance	ASTM C1027	4
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Class A
Scratch Hardness	MOHS	≥ 7
Breaking Strength	ASTM C648	≥ 250 lbf

Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An
Appointment



www.tileamerica.com



GREY