

AGATHA



ALINE



COSMOS



FLORA



REBECCA



SERAFINE



SKY



VEGAS

LILI CEMENT TILE

Cement Tile
8x8


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: 12 mm

Characteristics:	Norms:	Results
Water Absorption	ITCVN 6355 (1998)	3: 9.7%
Dynamic Coefficient of Friction (DCOF)	ANSI A137.1 (2012)	Section 9.6.1: 0.62
Breaking Bending Load	TCVN 6065 (1995)	Section 5.6: 1.18 kN
Relative Resistance to Deep Abrasive Wear	ASTM C1243-93 (2009)	222.6 mm ³

OLGA



Notes:

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com