

CAPITOL REEF



YOSEMITE



GRAND CANYON



KINGS CANYON



HOT SPRINGS



# National Parks LVT

Wood Look

7x48


# TILE

## AMERICA

### SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



### WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications. (i.e., restaurants, offices)

### PERFORMANCE DATA

THICKNESS 8.0 mm

CHARACTERISTIC	NORMS	RESULTS
Reaction to Fire	EN13501-1	Bfl-SI
Slip Resistance	DIN 51130 EN 13893	510 DS
Thermal Resistance	EN 12667:2001	0.038m2K/W
Curling	ISO 23999:2008	X: 0.08% Y: 0.07%
Residual Indentation	ISO 24343-1:2007	~0.01mm
Determination of Resistance - to Stains Chemical Resistance	ISO 26987:2008	Resistant
Squareness	ISO 24342:2007	X: 0.00mm~+0.05mm Y: 0.00mm~+0.05mm
Straightness	ISO 24342:2007	X: 0.00mm~+0.03mm Y: 0.00mm~+0.05mm
Peel Resistance	ISO 24345:2006	X: 65N/50mm Y: 65N/50mm

#### FEATURES:

- Specially engineered surfaces, coatings and wear layers keep the vinyl floors safe for all members of your family.
- Four-legged friends can lead to extra spills and accidents. Durable wear layers keep your floors protected and worry-free.
- Our floors won't absorb moisture around them making them perfect for spill-prone areas like bathrooms and kitchens.
- Our rigid core LVT plank is treated with proprietary technology that deters the growth of microorganisms that come in contact with its surface.
- All floors meet national ASTM requirements for scratch and slip resistance making them particularly useful in high-traffic commercial or residential spaces.

Book An  
Appointment



www.tileamerica.com