

FRASSINO



NOCE



OLMO



ROVERE



OAK LANE

Wood Look

8x48, 12x48 Massello


TILE

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: 9.5 mm

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5 %
Abrasion Resistance	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance	ISO 10545-13	A-LA-HA
Scratch Hardness	MOHS	≥ 6
Resistance to Stains	ISO 10545-14	Class 5

Notes:

Per ANSI standard A108.02,4.3.8.2, tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com