


DOLOMITE



PORTICO

Marble Look


13x22, 13x22 Nazca, Hexagon Mosaic,
Hoja Mosaic, Bullnose

TILE

AMERICA


SHADE VARIATION

OCEANIC




V2 - Slight Variation

Clearly distinguishable differences in texture and/or pattern within similar colors.



CASABLANCA



WEAR CODE


Matte: Class 4 All Residential and Light Commercial Applications.
Class 4 tiles may be used in all residential areas and light commercial applications.

Glossy: Class 1 Rated for wall application only

PERFORMANCE DATA

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5% (Matte); > 10% (Glossy)
Abrasion Resistance	ISO 10545-7	4 (Matte); 1 (Glossy)
Breaking Strength	ISO 10545-4	> 35 N/mm ² (Matte); > 12 N/mm ² (Glossy)
Dynamic Coefficient of Friction	AcuTest	≥ 0.42 (Matte)
Frost Resistance	ISO 10545-12	Frost Proof (Matte)
Chemical Resistance	ISO 10545-13	GLA/GHA
Resistance to Stains	ISO 10545-14	Class 5

ORO



MARFIL



Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com