


RIDGE

Slate Look 3x3 Mosaic, 12x24



SHADE VARIATION

V3 - Moderate Variation
While the colors present on a single piece of tile will be
indicative of the colors to be expected on the other tiles, the
amount of colors on each piece may vary significantly. For
example "that little bit of color" on one piece of tile may be the
primary color on the next piece.



BONE



WEAR CODE

White: Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including

those with heavy traffic and constant use.

Other Colors: Class 4 All Residential and Light Commercial Applications.

Class 4 tiles may be used in all residential areas and light commercial applications.

SAND





Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.5%
Abrasion Resistance	ISO 10545-7	4/5
Breaking Strength	ISO 10545-4	35-45 N/mm2
Dynamic Coefficient of Friction	AcuTest	> 0.50
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	А
Resistance to Stains	ISO 10545-14	Class 5



Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

