



DOLOMITE GRAY



DOLOMITE WHITE



SAVOY GRAY




SAVOY WHITE



VANTA GRAY



VANTA WHITE



SELECT

Stone Look


12x24, 24x48, 6x24, 24x24, 2x2 Mosaic, 3x3.5
Hexagon Mosaic, 2.72x3 Basket Mosaic

TILE

AMERICA

SHADE VARIATION

V2 - Slight Variation
Clearly distinguishable differences in texture and/or pattern within similar colors.



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

PERFORMANCE DATA

THICKNESS: 9mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.5 %
Breaking Strength	ASTM C648	≥ 400 lbf
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Unaffected
Scratch Hardness	MOHS	6

Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment

