

MULTICOLOR

SOLUMBRIA

Stone Look


12x24, 24x24, 24x48, Hexagon Mosaic, Bullnose

TILE

AMERICA

SHADE VARIATION

V4 - Random Color differences from tile to tile, so that one tile may have totally different colors from that of other tiles. Thus the final installation will be unique.



Note: This collection has an extreme variation in color. It varies between White, Blue and Beige.

WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

PERFORMANCE DATA

THICKNESS: 8 mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.5 %
Abrasion Resistance	ASTM C1027	4
Breaking Strength	ASTM C648	≥ 250 lbf
Dynamic Coefficient of Friction	AcuTest	≥ 0.42
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Class A
Scratch Hardness	MOHS	≥ 7

Notes:

It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An Appointment



www.tileamerica.com