**DUST** 

**TAUPE** 


# STEP IN

Stone & Metal Look 2x2 Mosaic, 12x24



SHADE VARIATION

V3 - Moderate Variation While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 5 Suitable for all Residential and Commercial Application. Class 5 tiles are suitable for all applications including those with heavy traffic and constant use.

### PERFORMANCE DATA

THICKNESS: 8.5 mm

GREY	

# **DARK**

Characteristics:	Norms:	Results
Water Absorption	ISO 10545-3	≤ 0.1 %
Abrasion Resistance	ISO 10545-7	5
Breaking Strength	ISO 10545-4	≥ 47 N/mm2
Dynamic Coefficient of Friction	AcuTest	0.7
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	Resistant
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Cleanable

## Notes:

Per ANSI standard A108.02, 4.3.82, joints on tiles longer than 15" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.



