

NOVA  
WHITE



IRON  
BLUE



LAVA  
GREY



RAVEN  
BLACK



# URBAN 2.0 TILE


Industrial Look  
2x2 Mosaic, 12x24, 3x24 Bullnose

AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Class 4 All Residential and Light Commercial Applications. Class 4 tiles may be used in all residential areas and light commercial applications.

## PERFORMANCE DATA

THICKNESS: 8 mm

Characteristics:	Norms:	Results
Water Absorption	ASTM C373	≤ 0.2%
Abrasion Resistance	ASTM C1027	4
Breaking Strength	ASTM C648	≥ 400 lbs
Facial Dimension	ASTM C499	In accordance
Thickness Dimension	ASTM C499	In accordance
Warpage Diagonal	ASTM C485	In accordance
Wedging	ASTM C502	In accordance
Scratch Hardness	MOHS	7
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Class A
Bond Strength	ASTM C482	≥ 200 psi
Dynamic Coefficient of Friction	AcuTest	≥ 0.42

## Notes:

Per ANSI standard A108.02,4.3.82, joints on tiles longer than 18" should not be staggered more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An  
Appointment



www.tileamerica.com