

WHITE  
SAND

# VINTAGE CEMENT


Cement Look  
12x24

# TILE AMERICA

SHADE VARIATION

V3 - Moderate Variation

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.



WEAR CODE

Ink Well: Class 3 Residential Applications.

White Sand: Class 4 All Residential and Light Commercial Applications.

## PERFORMANCE DATA

Characteristics:	Norms:	Results
Abrasion Resistance (PEI)	III/IV-V	ASTM C1027
Scratch Hardness / Glaze (Mohs)	8	MOHS Scale
Water Absorption (%)	≤ 0.50%	ASTM C373
Breaking Strength (Avg Lbf)	>600	ASTM C648
Chemical Resistance	Resistant	ASTM C650
Bonding Strength (psi)	50	ASTM C482
Frost Resistance	Resistant	ASTM C1026
Crazing Resistance	Resistant	ASTM C424
Thermal Shock	Resistant	ASTM C484
Stain Resistance	Resistant	ASTM C1378
Dynamic Coefficient of Friction*	≥ 0.55	ANSI A326.3

## Notes:

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile. Always inspect materials prior to installations. Always mix 2-3 cartons at a time while installing to insure the best blend.

Book An  
Appointment



www.tileamerica.com